

BON JOUR

DESIGNED BY PHILIPPE STARCK

BON JOUR
Ø45



LIGHT SOURCE
POWER LED
6W
575 lm
2700K/CRI 90
615 lm
3000K/CRI 90

BON JOUR
Ø90



LIGHT SOURCE
LED ARRAY
13,5W
1500 lm
2700K/CRI 90
1600 lm
3000K/CRI 90

BON JOUR
Ø145



LIGHT SOURCE
LED ARRAY
27W
2600 lm
2700K/CRI 90
2720 lm
3000K/CRI 90

□ 01 White
01 Blanco

■ CU Copper
CU Cobre

■ 14 Black
14 Negro



Description

LED luminaire for recessed mounting on plasterboard ceilings.
Once installed, the luminaire edge sticks out of the ceiling 10 mm creating a unique and very refined aesthetic effect. The luminaire's body is injected with aluminium. It is available in three sizes: Ø45 mm, Ø90 mm and Ø145 mm. Reflector made of anodized gloss aluminium with diffuser element made of polycarbonate.

Power Supply

Cabling included, ready to be powered by included remote driver.
Dali dimmable version available.
Versions without driver and 110V driver available on request.

Accessories

- Installation frame made from thermoplastic material for installation in suspended ceilings required for the Ø90 mm and Ø145 mm versions (not necessary for Ø45 mm version).
- Honeycomb and cross screening cylinder (included for Ø45 mm version).
- Screening accessories available for the ø145 version, with the same finishes as the decorative Bon Jour luminaire. See the Flos "The Home Collection" catalogue for more information.

Additional Information

IP44 protection grade.
Insulation class II.

Standard Compliance and Quality Marks

EN60598-1 European Technical Standards and any subsequent additions.

Descripción

Luminaria LED para ser instalada en falso techo. Una vez instalado, el borde de la luminaria sobresale del techo 10 mm creando un efecto estético único y refinado. Cuerpo de la luminaria realizado en aluminio inyectado. Disponible en tres tamaños: Ø45 mm, Ø90 mm y Ø145 mm. Reflector de aluminio anodizado brillante con elemento difusor realizado en policarbonato.

Unidades de Alimentación

Cableado incluido, disponible para conectar a equipo remoto.
Versión Dali dimmable disponible.
Versiones sin equipo y con equipo 110V disponibles bajo pedido.

Accesorios

- Marco de instalación realizado en material termoplástico para su instalación en falso techo, necesario para las versiones Ø90 mm y Ø145 mm (no es necesario para la versión de Ø45 mm).
- Accesorios honeycomb y cruceta de apantallamiento (incluidos en la versión de Ø45 mm).
- Accesorios de apantallamiento disponibles para la versión ø145, con los mismos acabados que la luminaria Bon Jour decorativa. Ver el catálogo Flos "The Home Collection" para más detalles.

Información Adicional

Índice de protección IP44.
Clase de aislamiento II.

Cumplimiento de Normativa y Marcas de Calidad

Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.



Ø45




Ø90 / Ø145

BON JOUR

Bon Jour Ø45

Light Source: Power LED DC 500 mA - 6W - 575 lm - 2700K/CRI 90 / 6W - 615 lm - 3000K/CRI 90



Recessed luminaire with LED light source. Remote 220/240V power supply included. It is necessary to anticipate a space for accessing the driver.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida. Necesario acceso al driver por registro.


Accessories included (honeycomb and screening crosspiece).

Accesorios incluidos (honeycomb y cruceta de apantallamiento).

2700K

Non Dimmable

- 03.2001.01
- Dali Version
- 03.2001.01.DA




Beam Angle: 24°			
h(m)	E(lx)	D(m)	
1	1715	0.42	
2	429	0.84	
3	191	1.27	
4	107	1.69	
5	69	2.11	

Luminous flux luminaire 352 lm

3000K

Non Dimmable

- 03.2006.01
- Dali Version
- 03.2006.01.DA




Beam Angle: 25°			
h(m)	E(lx)	D(m)	
1	1772	0.45	
2	443	0.89	
3	197	1.34	
4	111	1.79	
5	71	2.23	

Luminous flux luminaire 392 lm

2700K

Non Dimmable

- 03.2001.CU
- Dali Version
- 03.2001.CU.DA




Beam Angle: 24°			
h(m)	E(lx)	D(m)	
1	1556	0.43	
2	389	0.85	
3	173	1.28	
4	97	1.71	
5	62	2.14	

Luminous flux luminaire 335 lm

3000K

Non Dimmable

- 03.2006.CU
- Dali Version
- 03.2006.CU.DA




Beam Angle: 24°			
h(m)	E(lx)	D(m)	
1	1625	0.42	
2	406	0.83	
3	181	1.25	
4	102	1.67	
5	65	2.09	

Luminous flux luminaire 340 lm

2700K

Non Dimmable

- 03.2001.14
- Dali Version
- 03.2001.14.DA




Beam Angle: 23°			
h(m)	E(lx)	D(m)	
1	1739	0.41	
2	435	0.83	
3	193	1.24	
4	109	1.66	
5	70	2.07	

Luminous flux luminaire 352 lm

3000K

Non Dimmable

- 03.2006.14
- Dali Version
- 03.2006.14.DA




Beam Angle: 24°			
h(m)	E(lx)	D(m)	
1	1737	0.42	
2	434	0.84	
3	193	1.26	
4	109	1.68	
5	69	2.10	

Luminous flux luminaire 362 lm

Bon Jour Ø90

Light Source: LED Array DC 500 mA - 13,5W - 1500 lm - 2700K/CRI 90 / 13,5W - 1600 lm - 3000K/CRI 90



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.


Pre-installation frame must be ordered separately.

Marco de pre-instalación. Se ha de pedir por separado.

2700K

Non Dimmable

- 03.2003.01
- Dali Version
- 03.2003.01.DA




Beam Angle: 56°			
h(m)	E(lx)	D(m)	
1	793	1.07	
2	198	2.14	
3	88	3.21	
4	50	4.28	
5	32	5.35	

Luminous flux luminaire 736 lm

3000K

Non Dimmable

- 03.2007.01
- Dali Version
- 03.2007.01.DA




Beam Angle: 56°			
h(m)	E(lx)	D(m)	
1	852	1.06	
2	213	2.13	
3	95	3.19	
4	53	4.25	
5	34	5.32	

Luminous flux luminaire 781 lm

2700K

Non Dimmable

- 03.2003.CU
- Dali Version
- 03.2003.CU.DA




Beam Angle: 34°			
h(m)	E(lx)	D(m)	
1	1509	0.60	
2	377	1.21	
3	168	1.81	
4	94	2.42	
5	60	3.02	

Luminous flux luminaire 640 lm

3000K

Non Dimmable

- 03.2007.CU
- Dali Version
- 03.2007.CU.DA




Beam Angle: 35°			
h(m)	E(lx)	D(m)	
1	1495	0.63	
2	374	1.26	
3	166	1.89	
4	93	2.52	
5	60	3.14	

Luminous flux luminaire 655 lm

2700K

Non Dimmable

- 03.2003.14
- Dali Version
- 03.2003.14.DA




Beam Angle: 56°			
h(m)	E(lx)	D(m)	
1	538	1.07	
2	135	2.15	
3	60	3.22	
4	34	4.29	
5	22	5.37	

Luminous flux luminaire 383 lm

3000K

Non Dimmable

- 03.2007.14
- Dali Version
- 03.2007.14.DA




Beam Angle: 57°			
h(m)	E(lx)	D(m)	
1	544	1.08	
2	136	2.15	
3	60	3.23	
4	34	4.30	
5	22	5.38	

Luminous flux luminaire 389 lm

BON JOUR

Bon Jour Ø145

Light Source: LED Array DC 900 mA - 27W - 2600 lm - 2700K/CRI 90 / 27W - 2720 lm - 3000K/CRI 90



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Pre-installation frame must be ordered separately.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación remota 220/240V incluida.

Marco de pre-instalación. Se ha de pedir por separado.

2700K

Non Dimmable

- 03.2005.01
- Dali Version
- 03.2005.01.DA



Beam Angle: 57°

h(m)	E(lx)	D(m)
1	1099	1.10
2	275	2.19
3	122	3.29
4	69	4.38
5	44	5.48


Luminous flux luminaire 1099 cd

Luminous flux luminaire 1085 lm

3000K

Non Dimmable

- 03.2008.01
- Dali Version
- 03.2008.01.DA



Beam Angle: 58°

h(m)	E(lx)	D(m)
1	1143	1.10
2	286	2.20
3	127	3.31
4	71	4.41
5	46	5.51


Luminous flux luminaire 1143 cd

Luminous flux luminaire 1135 lm

2700K

Non Dimmable

- 03.2005.CU
- Dali Version
- 03.2005.CU.DA



Beam Angle: 39°

h(m)	E(lx)	D(m)
1	2189	0.71
2	547	1.42
3	243	2.13
4	137	2.83
5	88	3.54


Luminous flux luminaire 2189 cd

Luminous flux luminaire 1063 lm

3000K

Non Dimmable

- 03.2008.CU
- Dali Version
- 03.2008.CU.DA



Beam Angle: 39°

h(m)	E(lx)	D(m)
1	2227	0.71
2	557	1.42
3	247	2.13
4	139	2.84
5	89	3.55


Luminous flux luminaire 2227 cd

Luminous flux luminaire 1085 lm

2700K

Non Dimmable

- 03.2005.14
- Dali Version
- 03.2005.14.DA



Beam Angle: 56°

h(m)	E(lx)	D(m)
1	677	1.05
2	169	2.11
3	75	3.16
4	42	4.21
5	27	5.27


Luminous flux luminaire 677 cd

Luminous flux luminaire 484 lm

3000K

Non Dimmable

- 03.2008.14
- Dali Version
- 03.2008.14.DA



Beam Angle: 56°

h(m)	E(lx)	D(m)
1	697	1.06
2	174	2.11
3	77	3.17
4	44	4.23
5	28	5.28

Luminous flux luminaire 697 cd

Luminous flux luminaire 501 lm


BON JOUR

Accessories / Accesorios


Bon Jour Ø90

Pre-installation frame.  08.8974.00
Marco de pre-instalación.


Honeycomb and screening
crosspiece.  08.8976.14

Honeycomb y cruceta de
apantallamiento. 

Bon Jour Ø145

Pre-installation frame.  08.8975.00
Marco de pre-instalación.

Honeycomb and screening
crosspiece.  08.8980.14

Honeycomb y cruceta de
apantallamiento. 

Decorative screening
accessory.  08.8977.00

Accesorio decorativo de
apantallamiento.  08.8978.00

 08.8979.00
