

THE BLOCK OF LIGHT

DESIGNED BY KNUD HOLSCHER



LIGHT SOURCE
POWER LED
2,2W
154 lm
3000K/CRI 80

□ 01 Matt White
01 Blanco Mate

■ 72 Grey
72 Gris

■ 04 Matt Black
04 Negro Mate



Description

Embedded light fixture designed for indoor or outdoor use (IP65 protection grade). Available with next-generation LED light source in response to diverse signalling needs on pathways or stairways. Front made of aluminium with finish in matt white, grey or matt black.

Power Supply

Built-in, non-regulable constant current power supply of 100/240V, 50/60Hz. 700 mA current.

Accessories

Has galvanised steel accessories for embedding in concrete walls.

Additional Information

IP65 protection grade.
Insulation class I.
Suitable for installation on normally inflammable surfaces.

Standard Compliance and Quality Marks

EN60598-1 European Technical Standards and any subsequent additions.

Descripción

Luminaria empotrada concebida para uso interior o exterior (grado de protección IP65). Disponible con fuente de luz LED de última generación apta para responder a las diversas necesidades de señalizadores a lo largo de caminos de paso o escaleras. Frontal realizado en aluminio con acabado en pintura blanco mate, gris o negro mate.

Unidades de Alimentación

Fuente de alimentación de corriente constante 100/240V, 50/60Hz no regulable integrada. Alimentación a 700 mA.

Accesorios

Dispone de accesorio para empotrar en paredes de hormigón realizado en acero galvanizado.

Información Adicional

Índice de protección IP65.
Clase de aislamiento I.
Instalable sobre superficies normalmente inflamables.

Cumplimiento de Normativa y Marcas de Calidad



Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.



THE BLOCK OF LIGHT

TheBlockofLight


Light Source: Power LED 2,2W - 154 lm - 3000K/CRI 80



Semi-recessed signalling lamp for indoor or outdoor use. Non-regulable 100-240V, 50-60Hz power supply and 500 mm power cable included.

Luminaria de señalización semiempotrada para aplicación interior o exterior. Fuente de alimentación no regulable 100-240V, 50-60Hz integrada. Incluye cable de alimentación de 500 mm.

□ 09.3310.01C




Beam Angle: 45°

h(m)	E(lx)	D(m)
1	15	1.79
2	4	3.58
3	2	5.37
4	1	7.16
5	1	8.95

Luminous flux luminaire 85 lm

■ 09.3310.72C




Beam Angle: 45°

h(m)	E(lx)	D(m)
1	6	1.85
2	2	3.70
3	1	5.55
4	0	7.40
5	0	9.25

Luminous flux luminaire 50 lm

■ 09.3310.04C



Beam Angle: 41°

h(m)	E(lx)	D(m)
1	5	1.64
2	1	3.28
3	1	4.92
4	0	6.55
5	0	8.19

Luminous flux luminaire 40 lm

Accessories / Accesorios

Can for embedding in concrete.

Can para empotrar en hormigón.



08.8423.00