

WAN DOWNLIGHT

DESIGNED BY JOHANNA GRAWUNDER



LIGHT SOURCE
LED ARRAY
9,2W
945 lm
3000K/CRI 80



LIGHT SOURCE
QT-14
G9
max 40W

□ 30 White
30 Blanco

■ 05 Polished Aluminium
05 Aluminio Pulido

■ 14 Black
14 Negro

■ GN Green
GN Verde



Description

Ceiling recessed luminary providing direct light. Aluminum ring, available in chrome, shiny white, enameled green, and shiny black finishes. Low glare shield. Provided by two different ring due to fix the safety tempered glass, in shiny black and enameled green.

Reflectors

Sanded and chemically bleached aluminum reflector.

Power Supply

Pre-wiring included; ready for remote power supply.

Additional Information

IP44 protection grade.
Insulation class II, III depending on the versions.
Suitable for installation on normally inflammable surfaces.

Standard Compliance and Quality Marks

EN60598-1 European Technical Standards and any subsequent additions.

Descripción

Luminaria de luz directa para ser instalada empotrada a techo. Aro de aluminio disponible en acabado pulido, blanco brillante, verde esmaltado y negro brillante. Incorpora como antideslumbramiento. El producto lleva incorporados dos aros interiores intercambiables, que sujetan el cristal templado y el reflector, en acabado negro brillante o verde esmaltado.

Reflectores

Reflector de aluminio tratado con chorro de arena y blanqueado químicamente.

Unidades de Alimentación

Luminaria precableada para ser alimentada mediante equipo remoto.

Información Adicional

Índice de protección IP44.
Clase de aislamiento II, III, según las versiones.
Instalable sobre superficies normalmente inflamables.



Cumplimiento de Normativa y Marcas de Calidad

Luminaria conforme con la Normativa Técnica Europea EN60598-1 y partes segundas.

WAN DOWNLIGHT

Wan Downlight

Light Source: LED Array DC 500 mA - 9,2W - 945 lm - 3000K/CRI 80



Recessed luminaire with LED light source. Power supply not included.


Luminaria empotrable para fuente de luz LED. Fuente de alimentación no incluida.

Recommended power supply / Equipos recomendados*:

| | |
|-----------------|---------|
| Non Dimmable | 60.9160 |
| Dimmable 1-10V | 60.9188 |
| Dimmable Dali | 60.8847 |
| Dimmable Dali 2 | 60.9222 |
| Mains Dimming | 60.9411 |
| Casambi | 60.9207 |

* Refer to the Drivers chapter / Ver capítulo Drivers

- 03.6154.30A
- 03.6154.05A
- 03.6154.14A
- 03.6154.GNA





Beam Angle: 83°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 309 | 1.77 |
| 2 | 77 | 3.55 |
| 3 | 34 | 5.32 |
| 4 | 19 | 7.09 |
| 5 | 12 | 8.87 |

Wan Downlight


Light Source: QT-14 G9 - max 40W



Recessed luminaire with main voltage source.


Luminaria empotrable con alimentación directa a red.

- 03.6150.30
- 03.6150.05
- 03.6150.14
- 03.6150.GN



Beam Angle: 68°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 147 | 1.35 |
| 2 | 37 | 2.70 |
| 3 | 16 | 4.05 |
| 4 | 9 | 5.40 |
| 5 | 6 | 6.75 |



Beam Angle: 69°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 149 | 1.38 |
| 2 | 37 | 2.75 |
| 3 | 17 | 4.13 |
| 4 | 9 | 5.50 |
| 5 | 6 | 6.88 |