

Kelvin Led Wall support

Adjustable wall arm with rotating direct lighting, with double pantograph arm and adjustable head. Fused aluminum alloy body. Die-cast aluminum outer head, with injection-molded methacrylate diffuser. Painted CNC machined, extruded aluminum WALL FITTING. Extruded aluminum alloy square tube (12x12mm) structure, machined mechanically, so that it houses a stainless steel load-compensation spring and injection-molded acetal resin sliding blocks. 3 mm diameter wire outer tie rods. Available in white, anthracite, black or chrome finishes. The ON/OFF switch is electronic with optical mechanism located in the head.

Two possibilities to choose:

- PERSONAL MODE (orange switch) Dimm the light intensity you like.
- GREEN MODE (green switch) Now Kelvin LED becomes Green, saving even more energy thanks to his automatic compensation of the ambience light.



Mounting	Wall arm
Environment	Indoor
Weight	1.5 Kg
Light sources available	30 x TOP LED 7,5W 556lm total 3000K CRI 95 [i] GREEN MODE
Emergency	Without
Voltage	100-240/24V
Power	7,5W
Battery	No
Supply included	Yes

Cord Length 1800 mm

Materials Aluminum

- Colors**
- F3302030 - Glossy Black
 - F3302009 - Glossy White
 - F3302033 - Anthracite
 - F3314057 - Chrome

Certificate

